

KOV'R-KOTE®

PREMIUM, NONMETALLIC THREAD COMPOUND FOR USE ON DRILL COLLARS, DRILL PIPE, TUBING, & CASING

DESCRIPTION

KOV'R-KOTE® is the next logical step for the new generation premium compounds manufactured by **JET-LUBE®**. Based on the same patented Polymer Chemistry used to develop **POW'R-KOTE®, KOV'R-KOTE** is an economical, multifunctional, nonmetallic thread compound.

High strength polymers, graphite, and other naturally-occurring, extreme-pressure, and anti-wear additives lock together under pressure to resist galling, seizure, and downhole makeup. **KOV'R-KOTE's** exceptionally high film strength (1000 kgf measured by ASTM D-2596, 4-Ball EP Test) is among the highest in the industry for nonmetallic compounds. This makes it well suited for use on drill strings in any drilling environment and for bottom hole assemblies in most drilling situations.*

- Multifunctional (for use on both shouldered and interference threads)
- Nonmetallic
- Formulated with a patented blend of high-tech polymers, graphite and other nonmetallic additives
- Sticks to wet joints
- Aluminum-complex base for brushability and stability over a wide temperature range
- Contains additives for rust, corrosion, and oxidation protection
- Exceeds all performance specs described in API specification 5CT and set forth in API Recommended Practice 5A3
- Available in Arctic and Thermal Grades

DESCRIPTION

KOV'R-KOTE is designed to work as an anti-seize compound on shouldered connections, a running and sealing compound on interference-threaded connections, and as a storage compound for all types of threaded connections.

NSF H2 Reg. #127360

*For the most severe applications, **KOPR-KOTE®** or **POW'R-KOTE** is recommended.

PRODUCT CHARACTERISTICS

| | |
|--|------------------|
| Thickener | Aluminum Complex |
| Fluid Type | Petroleum |
| Dropping Point (ASTM D-566) | 450°F (232°C) |
| Specific Gravity | 1.2 |
| Density (lb/gal) | 10.2 |
| Oil Separation (ASTM D-6184) | <3.0 |
| Wt. % Loss @ 212°F (100°C) | |
| Flash Point (ASTM D-92) | >450°F (232°C) |
| NLGI Grade | 1 |
| Penetration @77°F (ASTM D-217) | 310 - 340 |
| Copper Strip Corrosion (ASTM D-4048) | 1A |
| 4-Ball (ASTM D-2596) | |
| Weld Point, kgf | 1000 |
| Friction Factor (relative to API-Modified) | 1.0 |
| Friction Factor (Per API RP 7G) | 1.0 |

PACKAGING

| Code No. | Container Size | Shipping Wt. |
|----------|----------------|--------------|
| 13923 | 1 gal. | 11 lb. |
| 13913 | 2½ gal. | 29 lb. |
| 13915 | 5 gal. | 54 lb. |
| 13924 | 15 gal. | 163 lb. |
| 13929 | 50 gal. | 540 lb. |

LIMITED WARRANTY

Jet-Lube, Inc. makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube, Inc. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube, Inc.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube, Inc. shall not be liable for incidental or consequential damages.

CORPORATE LOCATIONS

Houston, Texas—World Headquarters

0813

Maidenhead, England

Edmonton, Canada



JET-LUBE, INC.
4849 HOMESTEAD RD.,
SUITE 232
HOUSTON, TX 77028

WATS: 800-538-5823
PHONE: 713-670-5700
FAX: 713-678-4604
sales@jetlube.com
www.jetlube.com

OILFIELD

OILFIELD

OILFIELD

OILFIELD

OILFIELD