

High Performance , Type 455, 456




## High Performance

### Type 455, 456

Safety valves from the High Performance product group offer especially high capacity for their size. With a large quantity of nominal diameters (DN), pressure ranges and product options, they have proven themselves as a universal safety valve for many applications.

#### Approvals



#### Industries

- Chemical Industry
- Petrochemical Industry
- Power
- Technical Gases
- Food and Beverage Industry
- Pharmaceutical Industry

#### Further Links



[High Performance Catalog 2 \[DE\]](#)



[Instructions \[DE, EN, FR, IT, SP, RU, CN\]](#)



[Stückliste Type 455, 456 \[DE\]](#)

High Performance , Type 455, 456

## Datasheet

Product info	Metric unit	US unit
Key feature	High pressure with seat	High pressure with seat
Nominal diameter inlet	DN 25 - DN 100	1" - 4"
Nominal diameter outlet		
Pressure		
Actual orifice diameter d0	20 - 74 mm	0,79 - 2,91 in
Actual orifice area A0	314 - 4301 mm <sup>2</sup>	0,487 - 6,666 in <sup>2</sup>
Pressure	2,5 - 100 bar	36 - 1450 psig
Flange rating inlet	PN 63 - PN 160	CL150 - CL1500
Temperature acc. to DIN EN	-85 to 550 °C	-121 to 1022 °F
Temperature acc. to ASME	-29 to 538 °C	-20 to 1000 °F
Body material	1.0619, 1.4581, 1.7357	SA 216 WCB, SA 351 CF10M, SA 217 WC6
KUB-Materials		
Valve connection	Flange acc. to DIN EN 1092-1 ASME B 16.5 JIS 2220	Flange acc. to DIN EN 1092-1 ASME B 16.5 JIS 2220
Bellows	Stainless steel and elastomer	Stainless steel and elastomer
Type of loading	Spring loaded	Spring loaded
Approvals	PED/DIN EN ISO 4126-1, PED/AD 2000-Merkblatt A2, ASME Sec. VIII Div. 1, CRN, AQSIQ, EAC	PED/DIN EN ISO 4126-1, PED/AD 2000-Merkblatt A2, ASME Sec. VIII Div. 1, CRN, AQSIQ, EAC
Specials		

High Performance , Type 455, 456

## Options

Feature		Option Code
Disc	Metal sealing, with detachable lifting aid	J26 (Standard)
	Metal sealing, bull-race	J24 (Standard)
	Metal sealing, 1.4404	L44
	With soft sealing O-ring CR „K”	J21
	With soft sealing O-ring EPDM „D”	J22
	With soft sealing O-ring FKM „L”	J23
	With soft sealing O-ring FFKM „C”	J20
Seat/nozzle	Stellited seat / nozzle	L61
Bellows	Balanced bellows with closed bonnet	J78
	Balanced bellows with open bonnet	J68
	Balanced bellows for low set pressures with closed bonnet	J78J63 (on request)
	Balanced bellows for low set pressures with open bonnet	J68J63 (on request)
	Balanced bellows with special material Hastelloy	J81S15
	Balanced bellows with special material INCONEL	J83S15
Caps and levers	Screwed cap H2	
	Screwed plain lever H3	
	Screwed packed lever H4	
Spring	Spring, heat resistant	X01
	Spring, corrosive resistant 1.4310	X04
	Spring, INCONEL X-750	X08 (on request)
Test gag	For cap H2 (H1)	J70
	For lever H4 (H6)	J69
Bonnet	Closed	
	Open	
Heating jacket		
Lift indicator	For lifting device H4 (H6)	J39J93
Lift stopper	Ring	J51
	Actuate screw H2	J52
	Actuate screw H4	J50
Drain hole	G1/4"	J18
	G1/2"	J19
O-ring-damper	Cap H2	J65
	Packed lever H4	J66
Free of oil and grease		J85
NACE material test certificate	Sour gas resistance acc. to NACE MR0175; Certificate acc. to DIN EN 10204-3.1	N78

High Performance , Type 455, 456

Certificate acc. to DIN EN 10204-3.1

---

KUB bursting disc

---

-