# **EZY-TURN® BODY FILL**

### **GATE VALVE SEALANT**

#### **DESCRIPTION**

**EZY-TURN® BODY FILL** is a petroleum oil based sealant suitable for displacing water and foreign material in gate valve body cavities.

**EZY-TURN® BODY FILL** has shown it has excellent ability to remain the the body cavity during field service even though it is petroleum based. It has good metal adhesion and readily flows into hard to fill orifices and channels when pumped with a high-pressure lubricator.

**EZY-TURN® BODY FILL** should be used in applications where economy is required and hydrocarbon resistance is not a major concern.

- Mineral Oil
- Economical
- Pumpable
- Displaces Water
- Nonhazardous
- Highly Adhesive
- Corrosion Resistant
- Easy to Use

## **APPLICATIONS**

**EZY-TURN® BODY FILL** should be used in applications where economy is a factor and maximum hydrocarbon resistance is not required. It is good for close tolerance valves due to metal adhesion and superior flow properties under pressure.

In lower temperature applications or where greater pumpability is required us **EZY-TURN® ARCTIC BODY FILL** 

#### **RECOMMENDED CLEAN UP**

**Jet-Lube®** recommends using **EZY-OPEN™** or other safe oxygenated solvents for best clean up.

**EZY-OPEN™** is a nontoxic, nonflammable, biodegradable lubricant and cleaner specifically designed for valve cleaning applications.

Note: Not for use with oxygen for strong oxidizers such as hydrogen peroxide or sulfuric acid.

#### PRODUCT CHARACTERISTICS

Appearance	Smooth Sticky Paste	
Color	Grey to Black	
Thickner	Organophyllic Clay	
Cone Penetration, mm X 10 <sup>-1</sup>	265 - 280	
(ASTM D-217)		
Specific Gravity	0.94 Typical	
Density (lb/gal)	7.8	
Flash Point, °F (°C)	>435 (224)	
(ASTM D-92)		
Dropping Point	None	
(ASTM D-2265)		
pH Range	3 - 9	
Oil Separation, Wt %	5.0 Maximum	
(FTMS 791.B M 321.2)		
(ASTM D-6184)		
Temperature Range, °F (°C)	-20 to 350 (-29 to 177)	

## **PACKAGING**

Code No.	Container Size	Container
92522	10 lb	5 qt
92516	35 lb	5 gal
92524	120 lb	15 gal
92529	400 lb	50 gal

## **LIMITED WARRANTY**

Jet-Lube, Inc. makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube, Inc. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube, Inc.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube, Inc. shall not be liable for incidental or consequential damages.



